T20 Alarms Terminal

Gallagher T20 Alarms Terminal allows site wide alarms management.

Manage your alarms at the source

The T20 Alarms Terminal allows you to manage alarms without needing to return to the control room.

Features and benefits:

- Contemporary and intuitive user interface, with a 3.5" color screen and large back-lit keys

- IP66 rated environmental protection, and IK08 rated impact protection ensures you will be deploying a high quality, robust device

- Arm and disarm up to 50 alarm zones distributed across any system controllers

- Users are guided when acknowledging alarms or isolating inputs

- Display up to 200 unacknowledged alarms and manage up to 100 inputs

- Extensive perimeter management functions, including arming and disarming zones, acknowledging alarms, fence zone lockout for maintenance, and displaying fence voltage, battery voltage and fence controller temperature

- Multiple language support

- Integrated rear tamper

- Custom background images when in idle mode

- Fully configurable Mimic Panel reflecting the status of up to 8 inputs, outputs, or alarm zones

- Upgrade software in situ to keep your system up to date with latest technology developments (via HBUS).

Full access capability

The T20 is also available with full access reader functionality. See the *T-Series Reader Datasheet* to find out more.

security.gallagher.com

GALLAGHER

Gallagher T-Series accessories:

- **Protective Covers** - IK08 rating protects readers against vandal attacks and harsh environments
- **Dress Plates** - ensure a clean finish for sites upgrading their reader and terminal hardware
- **Spacers** – enforces a space between the reader and the mounting surface, allowing installations on metal surfaces whilst preserving credential read range
- **Bezels** – surrounds available in a variety of colours to suit décor.

Technical Specifications

Gallagher T20 Terminal		
POWER SUPPLY		
Voltage	9-16Vdc	
Idle current @ 13.6Vdc	110mA	
DIMENSIONS	mm	Inches
	179.5 x 95.7 x23	7.1 x 3.8 x0.9
CABLE SPECIFICATIONS	HBUS	Cardax IV
2 wire, RS485 data cable (Cat5, Belden 9842 or equivalent)	500M	200M
Gallagher HBUS Cable	500M	200M
ENVIRONMENTAL SPECIFICATIONS		
Temperature Range	-30º to + 70ºC (-22°F to +158°F)	
Humidity	95% non-condensing	
Environmental protection	IP66	
Impact rating	IK08	
UV Stability	Nil structural degradation for the life of the reader[†]	
Standards Compliance	All equipment complies with FCC, CE, UL, and C-Tick approvals. Please contact Gallagher for the latest list of approvals.	

* Read range may be reduced when reader is mounted on metal surfaces
[†] Prolonged exposure to high UV light environments can cause plastics to discolor
º For further cable specifications please refer to the Gallagher Security System Technical Reference Manual

T20 at Order codes	
T-Series Alarms Terminals	
C300464	T20 Alarms Terminal, White
C300463	T20 Alarms Terminal, Black
T-Series Dress Plates	
C300323	T20 Dress Plate, Black, Pk 5
T-Series Bezels	
C300292	T20 Bezel, Black, Pk 5
C300293	T20 Bezel, White, Pk 5
C300294	T20 Bezel, Silver, Pk 5
C300295	T20 Bezel, Gold, Pk 5
T-Series Spacers	
C300306	T20 Spacer, Black, Pk 5
C300307	T20 Spacer, White, Pk 5
C300312	T20 Protective Cover Spacer
T-Series Protective Covers	
C300272	T20 Protective Cover

T20 Protective cover
Dimensions (H X W X D)
193mm x 123mm x 32mm

security.gallagher.com

GALLAGHER